




CORRY MICRONICS, INC PRODUCT SPECIFICATION

CMIBF-WCDMA-1 Band Pass Cavity Filter

Parameters	Specifications
Frequency Range	1920~1980MHz
Insertion Loss	≤1.0dB
Ripple	≤0.5dB
Return Loss	≥18dB
Rejection	≥45dB@1800~1900MHz ≥45dB@2000~2110MHz ≥90dB@2110~2170MHz
Power Handling	100W
Port Connectors	N-Female
Impedance	50 Ω
Operating Temp.	-30°C~+75°C
Storage Temp.	-40°C~+85°C
Surface Finish	Black Paint
Dimensions	See Attached drawing (all dimensions are in Inches[mm])



CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 6/22/2018