




CORRY MICRONICS, INC PRODUCT SPECIFICATION

CLB-BPF-7RX BAND PASS FILTER BAND 7 RX

Passband	2500 MHz -2570 MHz
Passband Insertion Loss	0.5 dB max
Rejection	40 dB min @ 2170 MHz
VSWR	1.5:1 Max
Passband Ripple	± 0.25 dB
Power	10 W
Impedance	50 Ω
Dimensions	See Attached Drawing
Finish	Black Paint
Operating Temperature	-40°C to + 50°C
Connectors	Field Replaceable SMA, Female

Mechanical Drawing



1. Dimensions are in mm [Inches]
2. Tolerances: Outline drawing: ±0.2 [0.008]
Hole: ±0.2 [0.008]

CALL OUR SALES DEPARTMENT FOR MORE INFORMATION OR VARIATIONS OF THIS PRODUCT.

Corry Micronics, Inc. One Plastics Rd. - Corry, PA 16407
(724) 940-7556 ext. 138 Fax (724) 940-7707 www.cormic.com

Corry Micronics Inc. herein referred to CMI, believes this information to be accurate, but makes no warranties, expressed or implied as to the accuracy of this document. CMI assumes no liability for any injury, loss, damage, direct or consequential arising from the use of our products. User assumes all risk whatsoever in connection with its intended use. CMI also reserves the right to change this document without notice. 4/15/2019